

The Ephrata Bathhouse is plumbed inverted and must be winterized using the following procedure:

BATHHOUSE - WINTERIZATION PROCEDURE

Turn off the power to the water heaters and tape the breakers

Turn off & tape over the baseboard heater breakers

Turn off water using the long blue tool

Disconnect the water pipe (shark fitting under bathhouse deck)

Open the hot water fittings & drain the water heaters – connect hoses to heater drains

Disconnect all the toilet hookups at the wall
Open the supply valve & drain

Disconnect all the sink connections at the wall
Open the supply valves & drain

Remove the shower fitting – using the rotating hot/cold faucet cartridge (see graphic) tool

Drain shower lines & replace shower fittings

Flush the toilets

Put RV anti-freeze in all the sink traps

Put RV anti-freeze in all the shower traps

Put RV antifreeze in the toilets

Cycle the drain valve at the source end, leave closed after water stops draining

RV WATER BIBS WINTERIZATION PROCEDURE

Disconnect the hose from the bib to the RV connection

Open the farthest north and south RV water taps

Hook up compressed air to the RV water connection and blow the water out of the line thru the end bibs

Cycle all the RV water taps and repeat the blow out procedure, repeat as necessary

Close all the taps

RAMP WATER WINTERIZATION PROCEDURE

Turn off water using the long blue tool

Open the far end ramp water tap, including the below ground drain

Hook up the compressed air to the west ramp water tap and blow out the line.

Cycle the drain valve at the source end, leave closed after water stops draining

Repeat blowing out the line from the western tap

Add 1 gallon of RV antifreeze to the water line from the west ramp tap

Close all the taps

Return the blue tool to the shed

WATER SYSTEM FOR BUSHES

Open the drain at the north end

Shower faucet cartridge tool

